

# EvolutionRO<sup>1000</sup><sup>TM</sup>

*High-Flow Reverse Osmosis System*

**The Most Evolved Reverse Osmosis System on the Planet!**



**NOW INCLUDES  
1:1 RATIO!**

## **Includes:**

- KDF/Catalytic Carbon Pre-filter x1
- High-Flow Reverse Osmosis Membranes x2
- Inlet Pressure Gauge : liquid filled
- Garden Hose Connector : 1/2"
- Inline Shut-off Valve : 3/8"
- 6 ft. - White Inlet Line : 1/2"
- 10 ft. - Blue Purified Water Line : 3/8"
- 10 ft. - Black Drain Line : 3/8"
- Detailed Instructions and QuickStart Guide

- **1,000 Gallons Per Day or 42 Gallons Per Hour at Standard Line Pressure**
- **Reduces Parts Per Million of Total Dissolved Solids by 95%+**
- **SAVE MORE WATER!**
  - Standard 2:1 pre-plumbed
  - **Optional 1:1 ratio included**
- **Highest Flow Rates and the MOST EFFICIENT SYSTEM IN THE INDUSTRY!**

**HydroLogic<sup>TM</sup>**  
PURIFICATION SYSTEMS

# EvolutionRO<sup>1000</sup>™

High-Flow Reverse Osmosis System

## Options

Achieve the highest flow rates from **THE MOST EFFICIENT RO SYSTEM ON THE PLANET!** Capable of producing more than 1,000 GPD or 42 Gallons Per Hour of pure water at standard line pressure. Remove 95%+ of all Parts Per Million from your tap water. Save more water by running a 2:1 waste to product water ratio, or optional 1:1 ratio, which is included. Also, Includes custom KDF/Catalytic carbon filter for reduction of chlorine, chloramines, iron, sulfur and heavy metals - great for city or well water. Comes with all the necessary components for simple and quick setup.



### Pre-Evolution™ :

Adds 2 extra stages of pre-filtration - pleated, cleanable sediment filter and KDF85/55 w/Catalytic carbon filter. Recommended when using more than 150 gallons per week average.



### High-Flow De-Ionization Post Filter:

Delivers 000 PPM water. Removes last bit of Total Dissolved Solids to achieve the purest water possible.



### Electronic Shut-off Kit:

Includes solenoid valve and electronic float switch for precise control of water level in reservoir. \*Required when using a booster pump.



### Booster Pump:

For low inlet pressure under 40 psi. Boosts pressure to 60+ psi, giving faster flow rates of pure water.



### TDS Monitor:

Measure PPM of dirty water going in and pure water going out. Monitors performance of your system and membrane life.



### UV Sterilizer Kit:

Kills 100% of all bacteria and viruses. Ensures the safest water.



### Flowmaster:

Gallon meter and filter capacity monitor. Indicates when to change your pre-filter(s).



### Float Valve:

Fill any tank or reservoir unattended - **NO MORE FLOODS!**

### EvolutionRO<sup>1000</sup>™ Expected Flow Rates

Inlet Pressure	Gallons Per Day
40 psi	700
50 psi	900
60 psi	1100
70 psi	1300
80 psi	1500



Earth Friendly  
Company

**HydroLogic™**  
PURIFICATION SYSTEMS